

限用物質含有情況標示聲明書

Declaration of the Presence Condition of the Restricted Substances Marking

證書號碼/受理編號：(No.) 新申請案件

Certificate No./Application No.

商品標籤及商品檢驗標識：(Picture) 如附表一

Product Label and Commodity Inspection Mark.

樣張及其標示位置：(Description and Picture) 如附表二說明

Sample and its location

設備名稱： LED 燈管 <small>equipmentname</small>		型號(型式)：FOE/4F/830/20W/A-1, 系列型號如燈具主 型式及系列差異表，Type designation (Type)				
單元 Unit	限用物質及其化學符號 Restricted substances and its chemical symbols					
	鉛 Lead (Pb)	汞 Mercury (Hg)	鎘 Cadmium (Cd)	六價鉻 Hexavalent chromium (Cr ⁺⁶)	多溴聯苯 Polybrominate d biphenyls (PBB)	多溴二苯醚 Polybrominated diphenyl ethers (PBDE)
LED晶粒	○	○	○	○	○	○
燈帽	○	○	○	○	○	○
燈殼	○	○	○	○	○	○
驅動	○	○	○	○	○	○
備考1. “超出0.1 wt %”及“超出0.01 wt %”係指限用物質之百分比含量超出百分比含量基準值。 Note 1: “Exceeding 0.1 wt %” and “exceeding 0.01 wt %” indicate that the percentage content of the restricted substance exceeds the reference percentage value of presence condition. 備考2. “○”係指該項限用物質之百分比含量未超出百分比含量基準值。 Note 2: “○” indicates that the percentage content of the restricted substance does not exceed the percentage of reference value of 備考3. “-”係指該項限用物質為排除項目。 Note 3: The “-” indicates that the restricted substance corresponds to the exemption.						

茲切結保證所提供之商品限用物質含有情況標示內容係經執行測試作業或採適當之品質管理措施，並備置前述相關文件，確認正確無誤後提供貴局。並同意配合貴局執行後市場管理作業所需，依商品檢驗法第49條之規定，於限期28個工作天內提供相關證明文件以供審查。

I hereby ensure that “the presence conditions of the restricted substance” provided above have been proved by testing or appropriate quality control measures, and make sure the relevant documents provided are correct and ready. Also, I agree to cooperate with BSMI, as the Article 49 of the Commodity Inspection Act stipulates, to provide the relevant documents, if needed, for verification within 28 working days when BSMI carries out the market surveillance activities.

此致 to

經濟部標準檢驗局 The Bureau of Standards, Metrology

申請人： 鈞鴻光電股份有限公司

Applicant

負責人： 吳素華 (簽章)

Person in charge

(Signature)



中華民國 112 年 03 月 23 日

主型式及系列差異表

編號	燈管型號 (X1)	額定 電壓 (V)	額定 頻率 (Hz)	輸入電流 (A) (X2)	額定 功率 (W) (X3)	額定 光通量 (lm) (X4)	發光 效率 (lm/W) (X5)	額定 色溫 (X6)	相關 色溫 (K) (X7)	相移 因數	管徑 型式 (X8)	長度 (mm) (X9)	光學特性 代碼 (X10)	演色性	圖示
1	FOE/4F/830/18W/A- 1 (主測型號)	100-240	50/60	0.18-0.075	18.1	2160	119	F3000	3000	0.7	T25(T8) 四呎	1198	830/797	80	圖1
2	FOE/4F/840/18W/A	100-240	50/60	0.18-0.075	18	2250	125	F4000	4000	0.7	T25(T8) 四呎	1198	840/797	80	
3	FOE/4F/865/18W/A- 1	100-240	50/60	0.18-0.075	18.1	2160	119	F6500	6500	0.7	T25(T8) 四呎	1198	865/797	80	
4	FOE/4F/830/18W/A	100-240	50/60	0.18-0.075	18	2250	125	F3000	3000	0.7	T25(T8) 四呎	1198	830/797	80	
5	FOE/4F/865/18W/A	100-240	50/60	0.18-0.075	18	2250	125	F6500	6500	0.7	T25(T8) 四呎	1198	865/797	80	
6	FOE/2F/830/9W/A	100-240	50/60	0.09-0.03	9	1125	125	F3000	3000	0.7	T25(T8) 二呎	580	830/797	80	圖2
7	FOE/2F/840/9W/A	100-240	50/60	0.09-0.03	9	1125	125	F4000	4000	0.7	T25(T8) 二呎	580	840/797	80	

8	FOE/2F/865/9W/A	100-240	50/60	0.09-0.03	9	1125	125	F6500	6500	0.7	T25(T8) 二呎	580	865/797	80	
9	FOE/1F/865/5W/A	100-240	50/60	0.05-0.02	5	575	115	F6500	6500	0.7	T25(T8) 一呎	330	865/797	80	圖3